



SoupBinTCP for Nasdaq Nordic

Version 3.00.2
August 21, 2015

Confidentiality/Disclaimer**Confidentiality/Disclaimer**

This specification is being forwarded to you strictly for informational purposes and solely for the purpose of developing or operating systems for your use that interact with systems of NASDAQ OMX Group, Inc. and its affiliates (collectively, Nasdaq). This specification is proprietary to Nasdaq.

Nasdaq reserves the right to withdraw, modify, or replace this specification at any time, without prior notice. No obligation is made by Nasdaq regarding the level, scope or timing of Nasdaq's implementation of the functions or features discussed in this specification. The specification is provided "AS IS," "WITH ALL FAULTS". Nasdaq makes no warranties to this specification or its accuracy, and disclaims all warranties, whether express, implied, or statutory related to the specification or its accuracy. This document is not intended to represent an offer of any terms by Nasdaq. Whilst all reasonable care has been taken to ensure that the details contained herein are true and not misleading at the time of publication, no liability whatsoever is assumed by Nasdaq for any incompleteness or inaccuracies. By using this specification you agree that you will not, without prior written permission from Nasdaq, copy or reproduce the information in this specification except for the purposes noted above. You further agree that you will not, without prior written permission from Nasdaq, store the information contained in this specification in a retrieval system, or transmit it in any form or by any means, whether electronic, mechanical, or otherwise except for the purposes noted above. In addition you agree that you will not, without prior written permission from Nasdaq, permit access to the information contained herein except to those with a need-to-know for the purposes noted above.

Nasdaq® is a registered trademark, or service mark, of the NASDAQ OMX Group, Inc. in the United States and other countries.



Contents

1	OVERVIEW	1
1.1	SoupBinTCP Logical Packets	1
1.2	Protocol Flow	2
1.3	Heartbeats	2
1.4	End of Session Marker	2
1.5	Data Types	2
2	SOUPBINTCP PACKET TYPES	3
2.1	Debug Packet	3
2.2	Logical Packets Sent by a SoupBinTCP Server	3
2.2.1	Login Accepted Packet	3
2.2.2	Login Rejected Packet	3
2.2.3	Sequenced Data Packet	4
2.2.4	Server Heartbeat Packet	4
2.2.5	End of Session Packet	4
2.3	Logical Packets Sent by the SoupBinTCP Client	5
2.3.1	Login Request Packet	5
2.3.2	Unsequenced Data Packets	5
2.3.3	Client Heartbeat Packet	6
2.3.4	Logout Request Packet	6
3	SUPPORT	7
4	REVISION HISTORY	8

1 Overview

SoupBinTCP is a lightweight point-to-point protocol, built on top of TCP/IP sockets that allow delivery of a set of sequenced messages from a server to a client in real-time. SoupBinTCP guarantees that the client receives each message generated by the server in sequence, even across underlying TCP/IP socket connection failures. SoupBinTCP clients can send messages to the server. These messages are not sequenced and may be lost in the case of a TCP/IP socket failure.

SoupBinTCP is ideal for systems where a server needs to deliver a logical stream of sequenced messages to a client in real-time but does not require the same level of guarantees for client generated messages either because the data stream is unidirectional or because the server application generates higher-level sequenced acknowledgments for any important client-generated messages.

SoupBinTCP is designed to be used in conjunction with higher level protocols that specify the contents of the messages that SoupBinTCP messages deliver. The SoupBinTCP protocol layer is opaque to the higher-level messages. Note that unlike the ASCII version, messages may include any possible byte.

SoupBinTCP also includes a simple scheme that allows the server to authenticate the client on login.

Note:
 This specification is fully compatible with the SoupBinTCP 3.0 published on Nasdaq Trader:
<http://www.nasdaqtrader.com/content/technicalsupport/specifications/dataproducts/SoupBintcp.pdf>

1.1 SoupBinTCP Logical Packets

The SoupBinTCP client and server communicate by exchanging a series of logical packets.

Each SoupBinTCP logical packet has:

- a two byte big-endian length that indicates the length of rest of the packet (meaning the length of the payload plus the length of the packet type – which is 1)
- a single byte header which indicates the packet typ
- e a variable length payload

Table 1 - SoupBinTCP Logical Packet Structure

Two Byte Packet Length	Packet Type	Variable-length payload
------------------------	-------------	-------------------------

Notes:

The SoupBinTCP logical packets do not necessarily map directly to physical packets on the underlying network socket; they may be broken apart or aggregated by the TCP/IP stack.

The SoupBinTCP protocol does not define a maximum payload length.

Unlike the ASCII version, the payload may contain the line feed character or any character.

1.2 Protocol Flow

A SoupBinTCP connection begins with the client opening a TCP/IP socket to the server and sending a Login Request Packet. If the login request is valid, the server responds with a Login Accepted Packet and begins sending Sequenced Data Packets. The connection continues until the TCP/IP socket is broken.

Each Sequenced Data Packet carries a single higher-level protocol message. Sequenced Data Packets do not contain an explicit sequence number; instead both client and server compute the sequence number locally by counting messages as they go.

The sequence number of the first sequenced message in each session is always 1. Typically, when initially logging into a server the client will set the Requested Sequence Number field to 1 and leave the Requested Session field blank in the Login Request Packet. The client will then inspect the Login Accepted Packet to determine the currently active session. Starting at 1, the client begins incrementing its local sequence number each time a Sequenced Data Packet is received. If the TCP/IP connection is ever broken, the client can then re-log into the server indicating the current session and its next expected sequence number. By doing this, the client is guaranteed to always receive every sequenced message in order, despite TCP/IP connection failures.

SoupBinTCP also permits the client to send messages to the server using Unsequenced Data Packets at any time after the Login Accepted Packet is received. These messages may be lost during TCP/IP socket connection failures.

1.3 Heartbeats

SoupBinTCP uses logical heartbeat packets to quickly detect link failures. The server must send a Server Heartbeat packet anytime more than 1 second has passed since the server last sent any data. This ensures that the client will receive data on a regular basis. If the client does not receive anything (neither data nor heartbeats) for an extended period of time, it can assume that the link is down and attempt to reconnect using a new TCP/IP socket.

Similarly, once logged in, the client must send a Client Heartbeat packet anytime more than 1 second has passed since the client last sent anything. If the server doesn't receive anything from the client for an extended period of time (typically 15 seconds), it can close the existing socket and listen for a new connection.

1.4 End of Session Marker

The server indicates that the current session has terminated by sending an End of Session Message. This indicates that there will be no more messages contained in this session.

The client will have to reconnect and re-login with a new Session ID or a blank (space-filled) Session ID to begin receiving messages for the next available session.

1.5 Data Types

Character data fields are standard ASCII bytes.

Integer fields are binary big-endian values.

2 SoupBinTCP Packet Types

2.1 Debug Packet

A debug packet can be sent by either side of a SoupBinTCP connection at any time. Debug packets are intended to provide human readable text that may aid in debugging problems. Debug Packets should be ignored by both client and server application software.

Debug Packet				
Name	Offset	Len	Value	Notes
Packet Length	0	2	Integer	Number of bytes after this field until the next packet
Packet Type	2	1	“+”	Debug Packet
Text	3	Variable	Alpha-numeric	Free form human readable text

2.2 Logical Packets Sent by a SoupBinTCP Server

2.2.1 Login Accepted Packet

The SoupBinTCP server sends a Login Accepted Packet in response to receiving a valid Login Request from the client. This packet will always be the first non-debug packet sent by the server after a successful login request.

Login Accepted Packet				
Name	Offset	Len	Value	Notes
Packet Length	0	2	Integer	Number of bytes after this field until the next packet
Packet Type	2	1	“A”	Login Accepted Packet
Session	3	10	Alpha-numeric	The session ID of the session that is now logged into. Left padded with spaces.
Sequence Number	13	20	Numeric	The sequence number in ASCII of the next Sequenced Message to be sent. Left padded with spaces.

2.2.2 Login Rejected Packet

The SoupBinTCP server sends this packet in response to an invalid Login Request Packet from the client. The server closes the socket connection after sending the Login Reject Packet. The Login Rejected Packet will be the only non-debug packet sent by the server in the case of an unsuccessful login attempt.

Login Rejected Packet				
Name	Offset	Len	Value	Notes
Packet Length	0	2	Integer	Number of bytes after this field until the next packet

Packet Type	2	1	“J”	Login Reject Packet
Reject Reason Code	3	1	Alpha	See Login Reject Codes below.

Login Reject Codes	
Code	Explanation
“A”	Not Authorized. There was an invalid username and password combination in the Login Request Message.
“S”	Session not available. The Requested Session in the Login Request Packet was either invalid or not available.

2.2.3 Sequenced Data Packet

The Sequenced Data Packets act as an envelope to carry the actual sequenced data messages that are transferred from the server to the client. Each Sequenced Data Packet carries one message from the higher-level protocol. The sequence number of each message is implied; the initial sequence number of the first Sequenced Data Packet for a given TCP/IP connection is specified in the Login Accepted Packet and the sequence number increments by 1 for each Sequenced Data Packet transmitted.

Since SoupBinTCP logical packets are carried via TCP/IP sockets, the only way logical packets can be lost is in the event of a TCP/IP socket connection failure. In this case, the client can reconnect to the server and request the next expected sequence number and pick up where it left off.

Sequenced Data Packet				
Name	Offset	Len	Value	Notes
Packet Length	0	2	Integer	Number of bytes after this field until the next packet
Packet Type	2	1	“S”	Sequenced Data Packet
Message	3	Variable	Alpha-numeric	Defined by a higher-level protocol.

2.2.4 Server Heartbeat Packet

The server should send a Server Heartbeat Packet anytime more than 1 second passes where no data has been sent to the client. The client can then assume that the link is lost if it does not receive anything for an extended period of time.

Server Heartbeat Packet				
Name	Offset	Len	Value	Notes
Packet Length	0	2	Integer	Number of bytes after this field until the next packet
Packet Type	2	1	“H”	Server Heartbeat Packet

2.2.5 End of Session Packet

The server will send an End of Session Packet to denote that the current session is finished. The connection will be closed shortly after this packet, and the user will no longer be able to reconnect to the current session.

Server Heartbeat Packet				
Name	Offset	Len	Value	Notes
Packet Length	0	2	Integer	Number of bytes after this field until the next packet
Packet Type	2	1	"Z"	End of Session Packet

2.3 Logical Packets Sent by the SoupBinTCP Client

2.3.1 Login Request Packet

The SoupBinTCP client must send a Login Request Packet immediately upon establishing a new TCP/IP socket connection to the server.

Client and server must have mutually agreed upon the username and password fields. They provide simple authentication to prevent a client from inadvertently connecting to the wrong server.

Both Username and Password are case-insensitive and should be padded on the right with spaces.

The server can terminate an incoming TCP/IP socket if it does not receive a Login Request Packet within a reasonable period of time (typically 30 seconds).

Login Request Packet				
Name	Offset	Len	Value	Notes
Packet Length	0	2	Integer	Number of bytes after this field until the next packet
Packet Type	2	1	"L"	Login Request Packet
Username	3	6	Alpha-numeric	Username
Password	9	10	Alpha-numeric	Password
Requested Session	19	10	Alpha-numeric	Specifies the session the client would like to log into, or all blanks to log into the currently active session.
Requested Sequence Number	29	20	Numeric	Specifies the next sequence number in ASCII the client wants to receive upon connection, or 0 to start receiving the most recently generated message.

2.3.2 Unsequenced Data Packets

The Unsequenced Data Packets act as an envelope to carry the actual data messages that are transferred from the client to the server. These messages are not sequenced and may be lost in the event of a socket failure. The higher-level protocol must be able to handle these lost messages in the case of a TCP/IP socket connection failure.

Unsequenced Data Packet				
Name	Offset	Len	Value	Notes

Packet Length	0	2	Integer	Number of bytes after this field until the next packet
Packet Type	2	1	“U”	Unsequenced Data Packet
Message	3	Variable	Alpha-numeric	Defined by a higher-level protocol, but must not contain any embedded linefeeds.

2.3.3 Client Heartbeat Packet

The client should send a Client Heartbeat Packet anytime more than 1 second passes where no data has been sent to the server. The server can then assume that the link is lost if it does not receive anything for an extended period of time.

Client Heartbeat Packet				
Name	Offset	Len	Value	Notes
Packet Length	0	2	Integer	Number of bytes after this field until the next packet
Packet Type	2	1	“R”	Client Heartbeat Packet

2.3.4 Logout Request Packet

The client may send a Logout Request Packet to request the connection be terminated. Upon receiving a Logout Request Packet, the server will immediately terminate the connection and close the associated TCP/IP socket.

Logout Request Packet				
Name	Offset	Len	Value	Notes
Packet Length	0	2	Integer	Number of bytes after this field until the next packet
Packet Type	2	1	“O”	Logout Request Packet

3 Support

Specification documents can be located at:

<http://www.nasdaqomx.com/transactions/technicalinformation>

4 Revision History

Date	Revision	Change Description
June 8, 2015	3.0	Initial binary version for Nasdaq Nordic ¹ .
July 20, 2015	3.00.1	Corrected the Requested Sequence Number field in the Login Request Packet length to 20 char.
August 21, 2015	3.00.2	Corrected the Notes for the Message field in the Sequenced Data Packet, section 2.2.3.

¹ For the purpose of this document Nasdaq Nordic refers to, either each individually or all together, NASDAQ OMX Copenhagen A/S, NASDAQ OMX Helsinki Ltd, NASDAQ OMX Iceland hf. and NASDAQ OMX Stockholm AB. NASDAQ OMX Nordic may also include NASDAQ OMX Baltic that respectively refers to NASDAQ OMX Riga, NASDAQ OMX Tallinn and NASDAQ OMX Vilnius.